



MRP-10

Rescue tool of choice by search and rescue teams and ARFF first responders worldwide.



Professional Survival Equipment



MRP-10 Marine Rescue Platform

Always at the ready with the rapid response time needed to save lives.

Trusted by countless first response and search and rescue organizations worldwide, the quickly deployed and easy to board MRP-10 aids in getting large groups of distressed victims safely out of the water or down off a boat as fast as possible. Designed to get up to 10 people up and out of the water fast, the MRP-10 Inflatable Marine Rescue Platform is 100% reversible with dual chamber construction. The small and lightweight pack is perfect for boat, helicopter, and vehicle staging for rapid deployment.



Soft Valise Case:

Weight: 37 lbs. (16.8 kg)

Dimensions: 24 in. L x 12 in. (round)

Material: 1000 Denier Nylon Cordura™

Case Color: Orange

10 Person Rescue Platform:

Buoyancy Tube Diameter: 12 in. (30.48 cm.)

Freeboard: 12 in. (30.48 cm.)

Inflated Raft Dimensions: 114 in. (9' X 6") dia. x 12 in. H

Floor Area (Total): 37.7 sq. ft. (3.5 sq. m.)

Buoyancy in Salt Water: 1,306 lbs. (592.39 kg.)

Buoyancy in Fresh Water: 1,273 lbs. (577 kg.)

Cylinder Charge Pressure: 3,000 p.s.i.

Inflation System: Air Charge Inflation

Buoyancy Tube Fabric: USCG Approved Urethane Coated

Nylon Base Cloth. (Exceeds MIL-C_17415-16AA)

Standard Features

- Dual Chamber Reversible Configuration
- Painter/Static Line (length, 35 ft.)
- Lifelines (inner)
- Lifelines (outer)
- Reflective Patches
- Topping off Valve (4) /Pressure Relief Valve (2)

Standard Equipment

- Water Activated Exterior Locator Lights (2 ea.)
- Sea Anchor (automatically deployed)
- Heaving Ring and Line
- Raft Use Instructions/Owner's Manual
- Floating Knife
- Utility Bag
- Whistle
- Waterproof Solar Powered Flashlight
- Manual Inflation Pump
- Repair Clamps (2 ea.)

Optional Equipment

- Anodized Aluminum Deck Mounting Cradle
- USCG Approved Hydrostatic Release



SWITLIK
SIGNATURES



Air Charge Inflation
System



Heat Sealed Technology



Nylon-HD



Five Year Service
Interval

www.[SWITLIK](http://www.switlik.com).com